



|                         |                                       |
|-------------------------|---------------------------------------|
| IPX7                    |                                       |
| Size                    | 16.5cm                                |
| Type                    | 2-Way Coaxial System                  |
| Maximum power           | 250 W                                 |
| Continuous power output | 75 W                                  |
| Frequency response      | 34 Hz to 23 kHz                       |
| Sensitivity             | 88 dB (1 W/1 m) dB                    |
| Impedance               | 4 ?                                   |
| Mounting Depth          | 60 mm                                 |
| Woofer Cut-Out Hole     | ?127 mm                               |
| Woofer material         | PP                                    |
| Surround                | Trex plane                            |
| Voice Coil type         | Copper                                |
| Voice Coil bobbin type  | Polyimide film                        |
| Terminals               | FASTON Type                           |
| Magnets                 | Ferrite                               |
| Tweeter Type            | Dome                                  |
| 2-way Coaxial           |                                       |
| Speaker Grill           |                                       |
| Weight                  | 0.96 kg                               |
| Dimensions              | ?175 x 86 mm                          |
| Illumination            | Optional UD-ME650LED. Sold Separately |

Other

|             |                                        |
|-------------|----------------------------------------|
| Reliability | Waterproof IPX7, IPX6<br>UV ASTM D4329 |
|-------------|----------------------------------------|