??? ??????????? ?????

#### ???? ?????? 140,00 €

### ????????

### **Pure Power!**

The Pioneer PRO Shuriken series TS-M2010PRO Midrange Driver is a 20cm high efficiency speaker featuring a thick steel woofer basket design with a light weight yet rigid pulp cone, a large ferrite magnet and power motor assembly, a Copper Clad Aluminium Wire (CCAW) and an OFC short ring to reduce distortion and expand the wide range of crisp, loud and clear frequencies.

The Pioneer PRO Shuriken series TS-M2010PRO Midrange Driver is 400 W Max. / 180 W Continuous Power Handling (RMS).

The Pioneer PRO Shuriken series TS-M2010PRO Midrange Driver is the perfect balance of power handling and output to compliment the crisp highs from the TS-M1010PRO Bullet Tweeter.

Are You Ready To Go PRO?

The Pioneer Reference Series for Open Show series of speakers is designed specifically for those looking to produce some serious sound pressure levels. Inspired by Pioneer's history of record-breaking SPL competition, the new PRO series line of speakers is designed for loud sound pressure levels for open shows.

With an emphasis on efficiency and power handling, the PRO series line-up consists of bullet tweeters, mid bass drivers, and a subwoofer that can be mixed and matched to deliver impressive output, without requiring an impressive investment.

# **Specifications**



ShurikenThe Shuriken series of loud speakers is designed for everyday use. It is represented by a tweeter, mid-frequency speakers of 16 and 20 cm, and 30 cm subwoofer. These speakers have small installation depth, light weight, which does not weigh down the doors and allows them to be installed in any car.



PRO Pioneer Reference for Open ShowThe Pioneer Reference Series for Open Show is designed specifically for those looking to produce some serious sound pressure levels.

## **Main Features**

Shuriken

PRO Pioneer Reference for Open Show

Type
Maximum power
Continuous power output
Frequency response

Sensitivity

Impedance

20 cm Midrange Driver

400 W 180 W

45 Hz to 18 Hz 100 (1 W/1 m) dB

4?

Mounting Depth
Woofer Cut-Out Hole
Woofer material
Surround
Spider
Voice Coil type
Magnets
Weight
Dimensions
Accessories

78 mm
?184 mm
Paper
Cloth
Polyester Fibre
Copper Clad Aluminium Wire (CCAW)
Ferrite
4.7 (Pair, excluding accessories) kg
?206 x 85 mm
Speaker mounting screws