

??? ?????????????? ?????

???? ???????? 330,00 €

??????????

<https://www.youtube.com/watch?v=cyWLqm1WqSM>

A New Wave.

Pioneer's GM-ME500X1 is a Marine grade Class-D digital amplifier specifically designed for the marine environment, including features such as special painting, protective covers for the side panels and RCA terminal covers.

To prevent circuit shutdown, Pioneer's GM-ME500X1 digital amplifier circuit includes a "Protection Control System" senses its internal temperature and automatically moderates input level accordingly. Stable, durable circuitry lessens the risk of high input power for the unit to achieve 1 ? connection. This design enhances the flexibility to connect multiple subwoofers to a system.

For extra flexibility, easy installation is guaranteed thank to "Automatic Signal Sensing and Turn-On", which automatically detects an input signal and turns the amplifier on and off when connected via the speaker line input.

Variable Low Pass Filter (LPF) means you can adjust the audio frequency more according to the subwoofer characteristics and personal listening preferences. The GM-ME500X1 also includes a wired Bass Boost Remote Control.

The GM-ME500X1 has a sleek design thanks to its white cosmetics and hairline top plate enhancing the high quality sense of design and a total of 1600W.

Specifications

Speaker line input sensorconnect your existing OEM unit without the hassle of add-on adapters



Variable LPFadjust your low-pass filter frequency for greater audio system flexibility



Multi-block Terminalsmoothly connect up to 4 subs for high-power audio output

Class D

D-classenjoy first class sound and powerful volume on a versatile system at half the size of other units

Full specifications

Main Features

Channel(s)	1
Speaker Terminals	Block-type
LPF	Yes
Maximum power	1 x 600W (4?) 1 x 1000W (2?) 1600W Total
Continuous power output	1 x 300W RMS (4?) 1 x 500W RMS (2?) 1 x 800W RMS (1?)
Frequency response	10 Hz - 240 Hz
Input level control	RCA (0.2V - 6.5V) SP (0.8V - 16V)
Distortion	< 0.05 %
S/N ratio	> 100 dB
Chassis size (W x H x D)	265 mm x 215 mm x 60 mm
Bass Boost	Yes
Speaker line input sensor	Turn-on sensor
Bass Boost Remote	
Crossover Frequency	40 - 240Hz (-12 dB/oct) Hz
Mono	

Audio

RCA Terminals