

?????????????????????

????????? 115,00 €

-?? ?????? ??? ?????????? ?? ?????????? ??? ????? (????) ???? ????? ?? ?????? ??????? ??? 2109584031

??????????

?? ??????? ??? ?????? ?????? ??? ?????? ??? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?? 400WATT RMS, ?? ??????? ?????? ?????? ?????? ?????? ?????? , ?????????????????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? (100db). ?????? ?????? ?????? . ?? ?????? ?????? 2 inches ? ?????????? ??? ?????????? ?????? ?????? ?????? ?????? ?????? 97.5-105 db w/m . ? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? : 100? 24 db/octave - 150W RMS 200? 24 db/octave - 250W RMS 250HZ 24 db/octave - 400W RMS Specifications: MODEL: TRF 8MR400ND Nominal diameter:8inch Nominal impedance:4? Power RMS:200W Power PROGRAM RMS :400W Power MAX:400W Sensitivity (1w/1m):100 Frequency range:80-6000 Hz Voice coil diameter:? 50.88 mm Magnet dimension:?102*7mm X 1PCS Fs:80 Hz Re (D.C.):3.3? Basket:Die cast Aluminum Cone and dust cap:Paper Surround:Cloth Voice coil wire:CCAR Voice coil bobbin:KSV Magnet: ND Over all diameter:?211mm Bolt circle diameter:4holes-?5.5 mm ?197 mm Cut out diameter:?186 mm Depth:84 mm Net weight:1.5 kg Xmax:± 4mm