

?? ????????????? ???? ?

???? ??????? 17,00 €

????????

- ????? ?????: 172.1 g
- Roof antenna AM/FM

acv PRO OEM quality

Style: 16V

The acv basic antenna range offers good reception performance even under less than ideal conditions thanks to the selection of quality components and careful installation.

To optimise the reception of antennas, always ensure an optimum ground connection of the antenna base or the ground strap during installation.

Remove existing paint at the contact points with workshop materials and protect against corrosion with suitable contact paste and also treat the antenna rod thread and the antenna base thread to optimise contact.

**Note:**

In case of reception problems:

check antenna cable and antenna adapter

check vehicle for faults due to retrofit LED lighting  
check vehicle for faults due to retrofit voltage converter / power supply units / USB charging adapter  
check vehicle for faults due to retrofit digital power amplifiers

**Reception Mode:**  
AM/FM

**Installation:**  
installation point: roof rear  
drill hole round: 19 mm  
drill hole square: 15 mm x 15 mm  
rod length: 405 mm  
rod inclination: 60°  
rod type: 16V  
rod thread: M5

**Dimensions:**  
total high: 440 mm  
antenna socket: L = 60 mm / B = 43 mm  
antenna socket thread: M5

**Connections:**  
AM/FM: OEM Fiat

**Frequency range:**  
AM: 150 kHz - 1710 kHz  
FM: 87,5 MHz - 108 MHz

**Power consumption:**  
AM/FM: passiv

**Vehicle application:**  
Fiat Panda (ZAF 169) 10/2003 - 03/2013

**Replacement rod without socket:**  
Antenna rod AM/FM 41cm M5/M6 16V > item: 152000-23